



# 3-PC. SCREWED END BALL VALVE 2013KMD



## TESTED AND CERTIFIED FIRE SAFE TO API 607 API 608 DESIGN

### Size range :

1/2"~1" : 2000 WOG  
1-1/4"~2" : 1500 WOG  
2-1/2"~4" : 1000 WOG

### End Connection :

2011KMD - Socket Weld End  
2012KMD - Butt Weld End  
2013KMD - Screwed End

### Valve Materials :

316 Stainless Steel  
Carbon Steel

### Ball & Stem Material :

316 Stainless Steel

### Service Applications :

Hydraulic                      Chemical  
Steam                              Oil / Gas  
Oxygen                            Food Processing  
Vacuum                            Dry / Liquid Chlorine  
Thermal Fluids

### Seat Materials :

Teflon (PTFE)  
Reinforced Teflon (RTFE)  
TFE+25% Carbon  
DELTRIN  
PEEK  
TFM1600

**NACE MR0175**

- ISO 5211 Direct mounting pad
- ISO 15848 fugitive emission approved (option)
- Spring return handle (option)



8F, No.201, Sec. 2, Tiding Blvd., Neihu District, Taipei City 114, Taiwan R.O.C.  
TEL: +886-2-2658-5800                      FAX: +886-2-2658-2266 / 2799-7766

E-mail : [haitima@seed.net.tw](mailto:haitima@seed.net.tw)  
<http://www.haitima.com.tw>